

CPUID HWMonitor

File
View
Tools
Help

Sensor	Value	Min	Max
<div> <div></div> <div>VCELIKA</div> </div>			
<div> <div></div> <div>ASUSTeK Computer INC. P5V-V...</div> </div>			
<div> <div></div> <div>Voltages</div> </div>			
CPU VCORE	1.232 V	1.200 V	1.328 V
VIN1	3.232 V	3.184 V	3.264 V
+3.3V	3.056 V	3.040 V	3.072 V
+5V	4.973 V	4.946 V	4.973 V
+12V	11.776 V	11.456 V	11.904 V
+5V VCCH	4.785 V	4.758 V	4.812 V
VBAT	3.248 V	3.248 V	3.248 V
<div> <div></div> <div>Temperatures</div> </div>			
THRM	40 °C (103 °F)	40 °C (103 °F)	40 °C (103 °F)
TMPIN0	83 °C (181 °F)	55 °C (130 °F)	84 °C (183 °F)
TMPIN1	37 °C (98 °F)	35 °C (94 °F)	38 °C (100 °F)
TMPIN2	27 °C (80 °F)	-3 °C (24 °F)	46 °C (114 °F)
<div> <div></div> <div>Fans</div> </div>			
FANIN0	2445 RPM	2410 RPM	2481 RPM
FANIN1	1875 RPM	1854 RPM	1896 RPM
<div> <div></div> <div>Fans PWM</div> </div>			
FANPWM0	0 %	0 %	0 %
FANPWM1	0 %	0 %	0 %
FANPWM2	0 %	0 %	0 %
<div> <div></div> <div>WDC WD2500AAJB-00J3A0 ...</div> </div>			
<div> <div></div> <div>Temperatures</div> </div>			
Assembly	37 °C (98 °F)	37 °C (98 °F)	37 °C (98 °F)

Ready

NUM